

DISPLAY

AVAILABLE COLORS



Silver



Black



SHOWN IN BLACK

KEY FEATURES

- 47" Marquee Series True Outdoor All-Weather LED-LCD Digital Signage Display for permanent outdoor installation
- Ultra-Bright (2000 NIT), high-heat tolerant 47-inch full HD, 1080p LED-LCD screen
- Direct Sunlight-Readable
- High temperature Enhanced Solar Tolerance (EST) technology prevents isotropic backout
- Exterior designed to protect internal components from rain, snow, dust, insects, humidity, and salt air
- Powder-coated rust-proof aluminum exterior for strength and durability
- Multi-fan airflow system keeps the unit cool & dry in temperatures up to 122 degrees F.
- Ability to operate in cold weather (-40 degrees F).
- Ambient Light Sensor provides automatic dimming of backlight for night time viewing.
- Front tempered anti-reflective glass window provides added protection to LED-LCD screen, and safeguards against vandalism & abuse
- RS232 serial control with discrete on, off, and input control
- Rear IR receiver (located in the cable-entry compartment)
- Innovative water-tight Cable Entry System seals out moisture & allows for easy hook-ups
- Optional media player compartment door to house a digital media player, Pro:Idiom set top box, or fan-less PCs
- Weatherproof detachable 20W speaker module (optional)
- Side Control Lock-Out prevents unauthorized users from changing the programming
- Includes warranty and manual
- Landscape installation only. (Portrait model DS-4720P available Q3 2014)

<p>SCREEN</p>	<p>SCREEN 47-inch diagonal Color Active Matrix LED-LCD</p> <p>RESOLUTION 1920 x 1080 Full-HD 1080p</p> <p>SCREEN BRIGHTNESS 2000 nit</p> <p>ASPECT RATIO 16:9</p> <p>CONTRAST RATIO 1300:1</p>	<p>FRAME RATE 120 Hz</p> <p>VIEWING ANGLE 178° x 178°</p> <p>RESPONSE TIME 10.0 milliseconds</p> <p>TV FORMATS 1080p, 1080i, 720p, 720i, 480p, 480i</p> <p>SCREEN ORIENTATION Landscape Mode (Portrait available Q3, 2014)</p>
<p>CONNECTIONS</p>	<p>RF Antenna/CATV (ATSC/QAM/NTSC) x1</p> <p>HDMI HDMI™ Input x2</p> <p>COMPONENT YPbPr + Stereo Audio x2</p> <p>VIDEO COMPOSITE S-Video x1 and Composite Video x1, L/R Audio Inputs x1</p> <p>VGA VGA x 1</p> <p>POWER PORTS 12V</p> <p>PC 15-pin D-sub VGA plus Stereo Audio</p>	<p>CONTROL SET RS232 Serial, Discrete IR Control, Concealed IR Window</p> <p>AUDIO OUT SPDIF Audio(fixed), Analog 1/8" headphone jack (variable)</p> <p>SPEAKERS 20 WATT detachable speaker module (optional)</p> <p>INPUT POWER 100-240 VAC, 50-60 Hz 2.8 A Max</p>
<p>TEMPERATURE TOLERANCES</p>	<p>OPERATING TEMP -40° to 122° F. (-40° to 50°C.)</p> <p>NON-OP. TEMP -40° to 140° F. (-40° to 60°C.)</p> <p>(OFF MODE WITH POWER APPLIED) The non-operating temperature feature requires power to be applied</p>	
<p>PHYSICAL SPECS</p>	<p>ACCESSORIES INCLUDED Weatherproof remote control</p> <p>EXTERIOR Powder-coated aluminum</p> <p>EXTERIOR COLORS Black, Silver</p> <p>TV DIMENSIONS 44.75" W x 27.16" H (29.33in H with optional speakers) x 6.94" D</p> <p>TV WEIGHT 88.0 lbs without optional speaker, 92.0 lbs with optional speaker</p>	<p>SHIPPING DIMENSIONS 52.0"W x 42.0"H x 13.0"D</p> <p>SHIPPING WEIGHT 104.0 lbs without optional speaker, 108.0 lbs with optional speaker</p> <p>RESIDENTIAL WARRANTY Two-year parts and labor</p> <p>COMMERCIAL WARRANTY Two-year parts and labor</p>